

Product Name:	ASP-3
Description:	<p>CryoSafe ASP Class Liquid Nitrogen Tank</p> <p>The ASP Series includes:</p> <ul style="list-style-type: none"> Stainless steel tank with cabinet Recessed casters Keyed lid lock Leveling platform 6 ft. stainless steel armor plated transfer hose Sentry plus controller <p>Sentry Plus Auto-Fill Controller features:</p> <ul style="list-style-type: none"> • Power-Guard battery back up • Freeze-Guard overfill protection • Quick-chill temperature recovery • Auto-defog visibility safety • Splash-Guard false alarm prevention • Help button, user assistance • System log, alarm log, and temperature log with total 500,000 events • Serial port, 2 way communications • 4-20mA port • Ready for icSmart remote monitoring system • Keyless entry to power and control settings • Audio and visual alarms: <ul style="list-style-type: none"> ○ High temperature ○ High/low LN2 level ○ Valve stuck open ○ Lid open ○ Power failure ○ Sensor failure ○ Low LN2 supply ○ Unauthorized access ○ Usage warning ○ Temp calibration ○ Low battery • LN2 level readout +/- 1" (direct sensor LN2 contact) • LN2 supply monitor • LN2 usage calculation • Thermocouple auto-calibration • Temperature control • Digital temperature display • Temp display units: C, F, K, R • Automatic filling • Diagnostics at start-up • Maintenance reminder • 8 thermistor array

	<p>Model specifications:</p> <p>38,350 (2ml) total vial capacity</p> <p>870 total bag capacity</p> <p>590 liter liquid nitrogen capacity</p> <p>Static Evaporation Rate (liters/Day): 8</p> <p>Static Holding Time: 74 Days</p> <p>Power Requirement: 16.5 VAC</p> <p>Exterior Diameter (in/mm): 42/1066.8</p> <p>Overall Height (in/mm): 49/1244.6</p> <p>Usable Height (in/mm): 29/736.6</p> <p>Internal Diameter (in/mm): 39/990.6</p> <p>Weight empty (lbs./kg): 565/256.3</p> <p>Weight full (lbs./kg): 1616/733</p> <p>Shipping weight (lbs./kg): 835/378.8</p> <p>Three year parts and labor warranty</p> <p>Five year warranty on vacuum</p>
--	--